
Leyes.io Documentation

Release

[tosp]

Mar 06, 2017

Contents:

1	leyes package	1
1.1	Subpackages	1
1.2	Submodules	1
1.3	leyes.urls module	1
1.4	leyes.wsgi module	1
1.5	Module contents	1
2	Leyes.io	3
2.1	base package	3
2.2	tosp_auth package	4
3	Indices and tables	7
	Python Module Index	9

Subpackages

Submodules

leyes.urls module

leyes URL Configuration

The *urlpatterns* list routes URLs to views. For more information please see: <https://docs.djangoproject.com/en/1.10/topics/http/urls/>

leyes.wsgi module

WSGI config for leyes project.

It exposes the WSGI callable as a module-level variable named `application`.

For more information on this file, see <https://docs.djangoproject.com/en/1.10/howto/deployment/wsgi/>

Module contents

base package

Subpackages

Submodules

base.admin module

base.apps module

```
class base.apps.BaseConfig(app_name, app_module)
    Bases: django.apps.config.AppConfig
    name = 'base'
```

base.models module

base.test_views module

```
class base.test_views.TestBaseViews(methodName='runTest')
    Bases: django.contrib.staticfiles.testing.StaticLiveServerTestCase

    Integration test suite for testing the views in the app: base.

    Test the url for home and the basefiles like robots.txt and humans.txt

    browser
        Browser – Driver to navigate through websites and to run integration tests.

    setUp()
        Initialize the browser, before running the tests.
```

```
tearDown()  
    At the end of tests, close the browser  
  
test_home()  
    Test for url 'base:home'.  
  
    Visit the url of name 'home' and check it loads the content  
  
test_humans()  
    Test for url 'base:base_files(humans.txt)'.  
  
    Visit the url of humans.txt and check it loads the file  
  
test_robots()  
    Test for url 'base:base_files(robots.txt)'.  
  
    Visit the url of robots.txt and check it loads the file
```

base.urls module

base.views module

```
base.views.base_files(request, filename)  
base.views.home(request)
```

Module contents

tosp_auth package

Subpackages

Submodules

tosp_auth.admin module

tosp_auth.apps module

```
class tosp_auth.apps.TospAuthConfig(app_name, app_module)  
    Bases: django.apps.config.AppConfig  
    name = 'tosp_auth'
```

tosp_auth.models module

tosp_auth.tests module

tosp_auth.urls module

tosp_auth.views module

```
tosp_auth.views.logout(request)
```

Module contents

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

b

- `base`, 4
- `base.admin`, 3
- `base.apps`, 3
- `base.models`, 3
- `base.test_views`, 3
- `base.urls`, 4
- `base.views`, 4

l

- `leyes`, 1
- `leyes.urls`, 1
- `leyes.wsgi`, 1

t

- `tosp_auth`, 5
- `tosp_auth.admin`, 4
- `tosp_auth.apps`, 4
- `tosp_auth.models`, 4
- `tosp_auth.tests`, 4
- `tosp_auth.urls`, 4
- `tosp_auth.views`, 4

B

[base \(module\)](#), 4
[base.admin \(module\)](#), 3
[base.apps \(module\)](#), 3
[base.models \(module\)](#), 3
[base.test_views \(module\)](#), 3
[base.urls \(module\)](#), 4
[base.views \(module\)](#), 4
[base_files\(\)](#) (in module [base.views](#)), 4
[BaseConfig](#) (class in [base.apps](#)), 3
[browser](#) ([base.test_views.TestBaseViews](#) attribute), 3

H

[home\(\)](#) (in module [base.views](#)), 4

L

[leyes \(module\)](#), 1
[leyes.urls \(module\)](#), 1
[leyes.wsgi \(module\)](#), 1
[logout\(\)](#) (in module [tosp_auth.views](#)), 4

N

[name](#) ([base.apps.BaseConfig](#) attribute), 3
[name](#) ([tosp_auth.apps.TospAuthConfig](#) attribute), 4

S

[setUp\(\)](#) ([base.test_views.TestBaseViews](#) method), 3

T

[tearDown\(\)](#) ([base.test_views.TestBaseViews](#) method), 3
[test_home\(\)](#) ([base.test_views.TestBaseViews](#) method), 4
[test_humans\(\)](#) ([base.test_views.TestBaseViews](#) method), 4
[test_robots\(\)](#) ([base.test_views.TestBaseViews](#) method), 4
[TestBaseViews](#) (class in [base.test_views](#)), 3
[tosp_auth \(module\)](#), 5
[tosp_auth.admin \(module\)](#), 4
[tosp_auth.apps \(module\)](#), 4
[tosp_auth.models \(module\)](#), 4

[tosp_auth.tests \(module\)](#), 4
[tosp_auth.urls \(module\)](#), 4
[tosp_auth.views \(module\)](#), 4
[TospAuthConfig](#) (class in [tosp_auth.apps](#)), 4